

Description

CASA 383 is a non-flammable, water-based adhesive for bonding non-porous materials. It can also be used to bond melamine panels, HP laminates to aluminum and particle board, gypsum board, plywood, metal and certain other materials.

Advantages

- Non-toxic with no solvents
- Excellent temperature resistance
- Zero VOC
- Economical— up to 800 sq. ft. per gallon
- One part adhesive with short dry time
- Dyed blue for enhanced visibility

Application

Surfaces must be clean and dry. Spray an even coat of adhesive (approximately 4 to 5 grams per square foot) on both surfaces. Allow both to dry completely before bonding. When dry, adhesive will not transfer to fingers when touched. Drying time will be 5-15 minutes, depending upon atmospheric conditions such as temperature and humidity, as well as the amount of adhesive applied. Do not exceed 8 hours open time. Place both surfaces to be bonded in exact position desired. CASA 383 bonds immediately and cannot be repositioned. Clean up wet adhesive with CASA Quick Clean 6.

Packaging

- 5 gallon pails
- 55 gallon fiber drums
- 275 gallon disposable totes

Shelf Life

One year from the date of manufacture in unopened container.

Manufacturer's Statement

The statements and technical information contained in this technical data sheet are based on tests and data which CASA Adhesive, Inc. believes to be reliable, however the occurring and completeness of such statements and technical information is not guaranteed. CASA Adhesive, Inc. makes no warranty expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. User is responsible for determining if the product is fit for a particular purpose and is suitable for user's method of application.

CASA Adhesive, Inc.

206 Nance Road NE

Calhoun GA 30701

Phone: 888.685.0025

Fax: 888.781.5255

Email: casaadhesive@comcast.net

Web: casaadhesive.com